MATERIAL HANDLING & STORAGE

TECHNICAL SPECIFICATION SHEET

ELECTRIC INSTALL CART – STEEL

Electric lift and tilt · 1,102 lb (500 kg) · steel frame in Next Level blue

Lifts and tilts countertops and slabs electrically on two lifting columns, from flat to upright.



1,102 lb	5.9 in	25.6 in	258 lb
Load (500 kg)	Electric lift (150 mm)	Entrance width (650 mm)	Net weight (117 kg)

KEY FEATURES

- **Electric lift and tilt**
  Two linear actuators raise the frame 5.9 in (150 mm) and tilt it from flat to upright.
- **Through the door**
  29.5 in (750 mm) wide with a 25.6 in (650 mm) entrance width for kitchens and baths.
- **Flat or upright**
  Load a piece flat, then tilt it upright to roll it through the house.
- **Gentle on the stone**
  Nylon strips and stainless-steel ball transfers carry the piece.
- **Set at working height**
  Level height 31.5–37.4 in (800–950 mm) for seams and setting.
- **Next Level blue**
  Steel frame painted Next Level blue.

APPLICATIONS Countertop installation in kitchens and baths; truck to cabinet with finished pieces; seam work at working height; workshop handling.

ELECTRIC INSTALL CART – STEEL · TECHNICAL DATA

CART	
Length × width × height	59.1 × 29.5 × 31.5–37.4 in (1,500 × 750 × 800–950 mm)
Working (level) height	31.5–37.4 in (800–950 mm)
Lift range	5.9 in (150 mm)
Entrance width	25.6 in (650 mm)
Lift and tilt	Electric: two lifting columns with linear actuators

CART (CONT.)	
Contact parts	Nylon strips and stainless-steel ball transfers

RATING AND BUILD	
Load (factory)	1,102 lb (500 kg)
Frame	Structural steel (S235-equivalent), Next Level blue
Net / gross weight	258 / 375 lb (117 / 170 kg)
Packing	61.8 × 33.9 × 28.3 in (1,570 × 860 × 720 mm)

INCLUDED AS STANDARD

- Steel cart with two lifting columns
- Electric lift and tilt with control box
- Nylon strips and stainless ball transfers

DETAILS



Frame upright · Carrying a slab, tilted · Frame lowered flat

Factory data, 2026 (proforma invoice, drawings, data sheets and quotations). Capacities are the factory's ratings for the product itself; your floor, lifting equipment and loading method must suit the load. U.S. values first, metric in brackets; added conversions are approximate. Specifications are subject to change without notice. Images may show optional equipment. Document date: Nov 2026. Next Level Enterprises · www.nextlevel.plus · +1 941-900-3018 · sales@nextlevel.plus